

电流互感器 户内 环氧浇注

Current Transformer indoor resin casting type



配ZW7-40.5 户外真空断路器
Matches(ZW7-40.5)
vacuum circuit breaker

LZZBJ-35 型电流互感器

LZZBJ-35 Current Transformer

概述 Description

本系列电流互感器为环氧树脂浇注全封闭产品，适用于额定频率50Hz或60Hz，额定电压35kV及以下户内装置的电力系统中，作电能计量、电流测量和继电保护用。本产品符合IEC 185及GB1208-1997《电流互感器》标准。

The series current transformer of the type LZZB7-35W2 and LZZB7-35A are casting resins and fully enclosed. They are use for metering electric energy and current, relay protection in the electrical system up to rated frequency 50Hz or 60Hz and rated voltage 35kV. The transformers can be executed according to the standards IEC185 and GB12081997.

型号含义 Type designation



结构简介 Construction

本系列电流互感器为全封闭式柱式结构，耐污染及潮湿，尺寸小，重量轻，适用于任何位置、任意方向安装。

This current transformer is fully enclosed and posts type product. It has a good ability of antipollution and moisture proof. It is small and light. It can be mounted in any position you like.

技术参数 Technical data

- 1.产品符合标准GB1208和IEC185;
 - 2.额定绝缘水平：40.5/95/185kV;
 - 3.额定频率：50Hz, 60Hz;
 - 4.额定二次电流：5A, 1A;
 - 5.可制作测量级为0.2S或0.5S的高精度电流互感器;
 - 6.配35kV 户外真空断路器。
- 1.The current transformer are in accordance with GB1208 and IEC185 standards;
 - 2.Rated insulation level 40.5/95/185kV;
 - 3.Rated frequency 50Hz, 60Hz;
 - 4.Rated secondary current 5A, 1A;
 - 5.We can make high precision current transformers of class 0.2S or 0.5S for measuring;
 - 6.Can be fitted with 35kV outdoor vacuum cutout.

电流互感器 户内 环氧浇注

Current Transformer indoor resin casting type

额定一次电流 Rated primary current(A)	准确级次组合 Accuracy class and rated output(VA)	准确级及相应的额定输出 Accuracy class and rated output(VA)	4秒热电流 4-Second thermal current(kA)	额定动稳定电流 (Idyn) Rated dynamic current(KA)
50	0.2/0.2/0.2	0.2	15	7.5
	0.2/0.5/0.5	0.5	25	
75	0.5/0.5/0.5	10P10	50	
	0.2/0.2/10P10	0.2	15	
	0.2/0.5/10P10	0.5	25	12.5
100	0.5/0.5/10P10	10P10	50	
	0.2/10P10/10P10	0.2	15	
	0.5/10P10/10P10	0.5	25	20
150	110P10/10P10/10P10	10P10	50	
	0.2/0.2/0.2/10P10	0.2	15	
	0.2/0.5/0.5/10P10	0.5	25	30
200	0.5/0.5/0.5/10P10	10P10	50	
	0.2/0.2/10P10/10P10	0.2	15	
	0.2/0.5/10P10/10P10	0.5	25	40
300,400	0.5/0.5/10P10/10P10	10P10	50	
	0.2/10P10/10P10/10P10	0.2	15	
	0.5/10P10/10P10/10P10	0.5	25	50
600	0.2/10P10/10P10/10P10	10P10	50	
	10P10/10P10/10P10/10P10	0.2	15	
		0.5	25	80
800,1000		10P10	50	
1200,1500,1600		0.2	15	
		0.5	25	100
		10P10	50	

注：用户如有特殊要求，可与我厂协商后确定。

Note: Any special requirements can be negotiated with us.

外形尺寸 Overall Dimension

